

ARIB TR-B15  
Version 4.1-E1



**ENGLISH TRANSLATION**

**OPERATIONAL GUIDELINES FOR DIGITAL  
SATELLITE BROADCASTING**

**ARIB TECHNICAL REPORT**

**ARIB TR-B15 Version 4.1**

(Fascicle 1)

Established on October 26th, 1999

Revised on March 29th, 2000

Revised on May 31st, 2001

Revised on July 27th, 2001

Revised on January 24th, 2002

Revised on March 28th, 2002

Revised on July 25th, 2002

Revised on September 26th, 2002

Revised on March 26th, 2003

Revised on June 5th, 2003

Revised on July 29th, 2003

Revised on October 16th, 2003

Revised on February 5th, 2004

Revised on July 22nd, 2004

Revised on September 28th, 2004

Revised on December 14th, 2004

Revised on March 24th, 2005

Revised on September 29th, 2005

Revised on November 30th, 2005

Revised on March 14th, 2006

Revised on May 29th, 2006

Revised on September 28th, 2006

Revised on December 12th, 2006

Revised on May 29th, 2007

Revised on September 26th, 2007

Version 1.1

Version 1.2

Version 2.0

Version 2.1

Version 2.2

Version 2.3

Version 2.4

Version 2.5

Version 2.6

Version 2.7

Version 2.8

Version 2.9

Version 3.0

Version 3.1

Version 3.2

Version 3.3

Version 3.4

Version 3.5

Version 3.6

Version 3.7

Version 3.8

Version 3.9

Version 4.0

Version 4.1

**Association of Radio Industries and Businesses**

Attachment to Response

10/578,394

3 Pages

## **Volume 3**

# **BS Digital Satellite Broadcasting Operational Guidelines for Datacasting**

ARIB TR-B15  
Version 4.1-E1

### 5.3.1.6 Empty carousels usage

- An empty carousel is a data carousel with no DDB, where the numberOfModules field consists entirely of DII with zeroes.
- Empty carousels are used to switch between send/stop for component data without changing the ES description in the PMT, for instance, when a given component is required only for a particular period in an event.
- Switching between empty and non-empty carousels also switches the data\_event\_id.
- The rules for DII minimum transmission intervals (refer to 5.3.2) apply equally to empty carousels when they are transmitted.
- DII version upgrades are not generated during transmission of an empty carousel.
- At station selection (with auto\_start\_flag=1) and when an empty carousel is detected during data event switching, no error is generated but instead DII updating is monitored, and display of the startup document begins when the startup document first appears. For a data-enriched television program with auto\_start\_flag=0, if the entry component is an empty carousel at the point when the user presses the data button to activate the datacasting engine, the activation process is suspended and the device waits for the data button to be pressed again.
- If the carousel containing the document currently being viewed during multimedia content display changes to an empty carousel, a data event message ("DataEventChanged" interrupt event, identified via status=1) indicating the "change to an empty carousel" is generated for the BML document. This operation is the same irrespective the value of auto\_start\_flag and whether or not it is an entry component.
- Where an empty carousel is referenced but not in connection with station selection or data event switching for instance, via execution of a link between BML documents this results in an error equivalent to that which is generated when an ordinary carousel does not contain a reference module.

### 5.3.1.7 Basic receiver operations during datacasting program display

- The receiver continuously monitors the carousel DIIs of the following two components:
  1. Component DII containing the module being viewed
  2. Entry component DII.

The entry component DII is monitored in order to determine the timing for a forced return to the entry carousel in conjunction with local content switching for the entry component.
- Receiver response to data event switching on the component being viewed
 

The datacasting engine generates the "DataEventChanged" data event message for the document currently on display. It then discards the document, and obtains and displays a startup document contained in the module with moduleId=0. If data event switching results in an empty carousel, then after the document currently on display has been discarded the relevant component DII update is monitored, and if the empty carousel is removed by subsequent data event switching, a startup document is obtained and displayed. All synchronous and asynchronous interrupt events that occur after "DataEventChanged" are discarded, except for unload interrupt events. Where the epgTune/launchDocument/reloadActiveDocument function is employed within the "DataEventChanged" event handler, the startup document is not obtained and the processing is in accordance with the function specification.

—3-45—